



EL879969379US



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed


*AmBrewer*

Dated

18 June 2001

**THIS PAGE BLANK (USPTO)**

## Patents Form 1/77

Patents Act 1977  
(Rule 16)**The  
Patent  
Office**20JUL00 E554356-1 D01070  
P01/7700 0.00-0017738.6**Request for grant of a patent***(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)*

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

|    |  |  |  |   |
|----|--|--|--|---|
| 1. | Your reference   | P2638.A4/PAG   |  |   |
| 2. | Patent application number<br><i>(The Patent Office will fill in this part)</i>   | 0017738.6  |  | 20 JUL 2000                                   |
| 3. | Full name, address and postcode of the or of each applicant <i>(underline all surnames)</i>  | Hypoguard Limited<br>Dock Lane<br>Melton<br>Woodbridge<br>Suffolk IP12 1PE |  |   |
|    | Patents ADP number <i>(if you know it)</i>   |  |  |   |
|    | If the applicant is a corporate body, give the country/state of its incorporation  | United Kingdom   | 4135190001   |   |
| 4. | Title of the invention   | TEST MEMBER  |  |   |
| 5. | Name of your agent <i>(if you have one)</i>  | DUMMETT COPP   |  |   |
|    | "Address for service" in the United Kingdom to which all correspondence should be sent <i>(including the postcode)</i>   | 25 THE SQUARE<br>MARTLESHAM HEATH<br>IPSWICH<br>IP5 3SL                    |  |   |
|    | Patents ADP number <i>(if you know it)</i>   | 6379001  |  |   |
| 6. | If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and <i>(if you know it)</i> the or each application number   | Country  | Priority application number<br><i>(if you know it)</i> | Date of filing<br><i>(day / month / year)</i> |
| 7. | If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application   | Number of earlier application  | Date of filing<br><i>(day / month / year)</i>          |   |
| 8. | Is a statement of inventorship and of right to grant of a patent required in support of this request? <i>(Answer 'Yes' if:</i><br>a) <i>any applicant named in part 3 is not an inventor, or</i><br>b) <i>there is an inventor who is not named as an applicant, or</i><br>c) <i>any named applicant is a corporate body.</i><br>See note (d)) | YES  |  |   |

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

|  |             |   |
|--|-------------|---|
| THE PATENT OFFICE<br>A<br>20 JUL 2000<br>RECEIVED BY FAX | Description | 6 |
|  | Claim(s)    | 3 |
|  | Abstract    | 1 |
|  | Drawing(s)  | 1 |

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translation of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) 1Request for preliminary examination and search (*Patents Form 9/77*) 1Request for substantive examination (*Patents Form 10/77*) 1Any other documents  
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date


  
DUMMETT COPP

20 July 2000

12. Name and daytime telephone number of person to contact in the United Kingdom

DR PETER A GEMMELL  
01473 660600**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

THE PATENT OFFICE

A

25 JUL 2000

The  
Patent  
OfficeStatement of inventorship and of  
right to grant of a patent

NEWPORT

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference

P2638.A4/PAG

2. Patent application number  
(if you know it)

3. Full name of the or of each applicant

HYPOGUARD LIMITED

4. Title of the invention

TEST MEMBER

5. State how the applicant(s) derived the right  
from the inventor(s) to be granted a patent

BY VIRTUE OF EMPLOYMENT

6. How many, if any, additional Patents Forms  
7/77 are attached to this form  
(see note (c))7. I/We believe that the person(s) named over the page (and on  
any extra copies of this form) is/are the inventor(s) of the invention  
which the above patent application relates to.

Signature

Date

Dummett Copp

20 July 2000

8. Name and daytime telephone number of  
person to contact in the United KingdomDr Peter A Gemmell  
01473 660600

## Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

**Enter the full name, address and postcodes of the inventors in the boxes and underline the surnames**

Patents ADP number (if you know it):

79 44770001

Patents ADP number (if you know it):

**Have you signed the form?**

Patents ADP number (if you know it):

DUPLICATE

- 1 -

## TEST MEMBER

## BACKGROUND OF THE INVENTION

## 5 1. Field of the Invention

The present invention relates to a test member for measuring the concentration of an analyte in a fluid sample, notably to a test strip for analysing blood  
10 glucose or other analytes in bodily fluids. The invention also provides a test device which includes a stack of the test members.

15 2. Background of the Invention

Diabetics regularly need to test samples of their blood to determine the level of blood glucose. The results of such tests may be used to determine levels of medication needed to treat the diabetes at the time. In one known type of  
20 system, disposable sensors are used to test the blood. The sensors typically take the form of test strips which are provided with a reagent material that will react with blood glucose to produce an electrical signal. Conductive tracks on the test strip relay the electrical signal to a  
25 meter which displays the result. After a sample of blood has been applied to the test strip and the measurement has been taken, the test strip is disposed of. In order to couple the conductive tracks on a test strip with the meter, the test strip needs to be inserted into a sensor  
30 holder prior to the start of testing. The sensor holder has corresponding electrodes which are brought into electrical contact with the conductive tracks of the test strip. Alternatively, the reagent in the test strip may undergo a visible colour change, the magnitude of which is  
35 used to determine the analyte concentration in the applied

- 2 -

fluid.

It is known to provide a stack of disposable circular test elements in a cylindrical housing, the stack being urged  
5 towards a test station by a spring to form a liquid-proof seal, for example as described in WO 94/10558.

A problem with providing disposable test members in a stack is that the working area to which the fluid sample  
10 will be applied can become scuffed, particularly when a compressive force is applied to the stack by a spring.

It is an object of the present invention to provide an improved test member suitable for use in test devices that  
15 employ test members in a stack.

#### SUMMARY OF THE INVENTION

According to an aspect of the present invention there is  
20 provided a test member suitable for use in a test device for testing of analyte concentration in a fluid to be applied thereto, the test member comprising a base member having a working area to which the fluid is to be applied, containing a reagent which is reactive to the said analyte  
25 to produce an electrical signal or a colour change, and a non-working area adjacent to the working area, wherein the total thickness of the test member in at least a portion of the non-working area is at least as great as the total thickness of the test member in the working area.

30

By making the non-working area at least as thick as the working area, scuffing or abrasion of the working area in a stack can be reduced. Moreover, if a compressive load is applied to a stack of the test members, this may be  
35 spread out over a greater area, ther by reducing the



- 3 -

possibility of compressive damage to the working area.

In a preferred embodiment, at least a part of the non-working area is of greater total thickness than the  
5 thickness of the working area. This further reduces the likelihood of damage to the working area by scuffing or abrasion when in a stack. The difference in thickness is preferably from 1 to 20  $\mu\text{m}$ , notably from 5 to 10  $\mu\text{m}$ .

10 The test member may be of any desired shape for a particular application; however, typically the test member will be an elongate test strip. For convenience hereinafter, the invention will be described with  
15 reference to such a test strip. However, it is to be understood that the invention is not limited to this embodiment.

In one embodiment, the reagent is reactive to the analyte to produce a visible colour change. Alternatively, the  
20 reagent may react with the analyte to produce an electrical signal which is measured and displayed by a meter. In this embodiment, the working area has electrodes which are electrically connected to electrode tracks in the non-working area, and at least part of the  
25 tracks are exposed for connection to electrodes of a meter. The invention will be described hereinafter with reference to this embodiment.

To build up the working area, a plurality of layers are  
30 sequentially applied to the base layer, for example by screen printing, typically with curing or drying steps between the application steps. The layers which are printed typically comprise electrode patterns, a reagent layer, and a mesh layer (for spreading out an applied  
35 fluid). As a result of the application of these layers,

- 4 -

the working area of a conventional electrochemical test strip is typically about 100  $\mu$ m thicker than the non-working area, which contains the electrode tracks and, typically, a dielectric layer. A stack of 100 test strips will therefore be about 10 mm thicker in the working area than in the non-working area. In a test strip in accordance with the present invention, at least a part of the non-working area may be made thicker by any suitable means. Suitable means include, for example: a printed relief ink; an applied pad or tape; embossing of the base layer or an intermediate layer; or an extension of the mesh layer from the working area.

The invention also provides a test device which uses the test members. Accordingly, another aspect of the invention provides a test device for testing of analyte concentration in a fluid to be applied thereto, the device including a plurality of test members arranged in at least one stack, each of said test members carrying reagent means for producing an electrical signal or a colour change in response to the concentration of analyte in an applied fluid; wherein each of the said test members comprises a base member having a working area to which the fluid is to be applied, containing the said reagent means, and a non-working area adjacent to the working area, wherein the total thickness of each test member in at least a portion of the non-working area is at least as great as the total thickness of each test member in the working area.

The test members may be held under a compressive load by spring means.

- 5 -

## BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be further described, by way of example, with reference to the following drawing in which:

5

Figure 1 is a top plan view of a test strip in accordance with the present invention.

## DETAILED DESCRIPTION

10

The exemplified test strip comprises a planar base member 2, in this example of poly(butylene terephthalate) (PBT) (Valox® FR-1 from GE Plastics). The strip is 30 mm x 5.5 mm, and 0.5 mm thick. A working area 4 is of conventional construction, comprising a plurality of electrodes, a reagent layer in intimate contact with the electrodes, and a mesh layer for spreading out a drop of fluid to be received on the working area. Electrode tracks 12, for example of carbon, in the non-working area 8 of the test strip are connected to the electrodes in the working area 4 in known manner. Also in known manner, a dielectric layer 6 is printed around the working area 4 so as to overlie a portion of the electrode tracks 12, leaving just the ends of the tracks exposed for connection to corresponding electrodes on a meter. The layers are applied to the base member as inks, by screen printing. Each ink layer is about 10 to 20  $\mu\text{m}$  thick, and the mesh is about 59 to 67  $\mu\text{m}$  thick. The working area 4 has a total thickness which is about 100  $\mu\text{m}$  thicker than the non-working area 8 up to the dielectric layer 6.

To increase the thickness of parts of the non-working area, a high relief ink 10 has been printed in four strips. The high relief ink has a dried thickness such

- 6 -

that the total thickness of the non-working area to which the high relief ink 10 has been applied is slightly greater than the total thickness of the test strip in the working area 4. Thus, when a stack of such test strips is formed, and a compressive load is applied to the stack by a spring, the working area 4 will not bear all the compressive load. If the test strips are used in a device which requires one strip to be slid out before being used to test analyte concentration in a fluid, scuffing of the test area will be reduced compared to a conventional test strip in which the working area stands proud of the non-working area.

Although the invention has been illustrated with reference to the use of a high relief ink printed in strips, it will be understood that it is not limited to this embodiment. The ink could be printed as a continuous block, and it could entirely surround the working area if desired. Instead of, or in addition to, the high relief ink, other means could also be provided to increase the thickness of the non-working area, for example: an applied pad or tape; embossing of the base layer or an intermediate layer; or an extension of the mesh layer from the working area into the non-working area.

25

- 7 -

## CLAIMS

1. A test member suitable for use in a test device for testing of analyte concentration in a fluid to be applied thereto, the test member comprising a base member having a working area to which the fluid is to be applied, containing a reagent which is reactive to the said analyte to produce an electrical signal or a colour change, and a non-working area adjacent to the working area, wherein the total thickness of the test member in at least a portion of the non-working area is at least as great as the total thickness of the test member in the working area.
2. A test member as claimed in claim 1, wherein the total thickness of the test member in at least a part of the non-working area is greater than the total thickness of the test member in the working area.
3. A test member as claimed in claim 2, wherein the total thickness of the test member in at least a part of the non-working area is from 1 to 20  $\mu\text{m}$  greater than the total thickness of the test member in the working area.
4. A test member as claimed in claim 2, wherein the total thickness of the test member in at least a part of the non-working area is from 5 to 10  $\mu\text{m}$  greater than the total thickness of the test member in the working area.
5. A test member as claimed in any one of the preceding claims wherein the said at least a part of the non-working area includes a printed ink layer.
6. A test member as claimed in any one of the preceding claims wherein the said at least a part of the non-working area includes an adhered tape or pad.

- 8 -

7. A test member as claimed in any one of the preceding claims wherein the said at least a part of the non-working area includes an embossed structure.

5

8. A test member as claimed in any one of the preceding claims wherein the said at least a part of the non-working area includes a mesh layer.

10 9. A test member as claimed in claim 8, wherein the said mesh layer is continuous with a mesh layer in the working area.

15 10. A test member as claimed in any one of the preceding claims, wherein the said reagent produces an electrical signal in response to the concentration of analyte in an applied fluid, the test member having a plurality of electrode tracks for transmitting the electrical signal, the said electrode tracks being exposed on a portion of  
20 the non-working area for connection to corresponding electrodes of a meter of a test device.

11. A test member as claimed in any one of the preceding claims, wherein the test member is an elongate test strip.

25

12. A test member as claimed in any one of the preceding claims, suitable for use in testing for the concentration of glucose in blood.

30 13. A test member suitable for use in a test device for testing of analyte concentration in a fluid to be applied thereto substantially as herein described with reference to the drawing.

35 14. A test device for testing of analyte concentration in

- 9 -

- a fluid to be applied theret , the device including a plurality of test members arranged in at least one stack, each of said test members carrying reagent means for producing an electrical signal or a colour change in response to the concentration of analyte in an applied fluid; wherein each of the said test members comprises a base member having a working area to which the fluid is to be applied, containing the said reagent means, and a non-working area adjacent to the working area, wherein the total thickness of each test member in at least a portion of the non-working area is at least as great as the total thickness of each test member in the working area.
15. A test device as claimed in claim 14, wherein the at least one stack of test members is held under a compressive load by spring means.

- 10 -

# ABSTRACT

## TEST MEMBER

5 A test member suitable for use in a test device for  
testing of analyte concentration in a fluid to be applied  
thereto comprises a base member (2) having a working area  
(4) to which the fluid is to be applied, containing a  
reagent which is reactive to the said analyte to produce  
10 an electrical signal or a colour change, and a non-working  
area (8) adjacent to the working area (4). The total  
thickness of the test member in at least a portion of the  
non-working area (8) is at least as great as the total  
thickness of the test member in the working area (4). The  
15 invention also provides a test device which includes a  
stack of the test members.

Figure 1

20



1/1




FIG. 1

**THIS PAGE BLANK (USPTO)**